

Filex 63 COLOR

Cinematic LED Ellipsoidal Light


The G3 COLOR is a cinema-grade 90W full-color ellipsoidal with razor-sharp cuts and a unique 360 degree rotating barrel. The beam produced from either the 19° or 36° tube lens is uniformly and bright without any color splitting. At the core of the G3 is the latest generation of Fiilex's patented Dense Matrix LED that adheres to the highest standards of dimming and color calibration. The G3 ellipsoidal gives you full control and can be rigged and hidden anywhere on production sets.




FEATURES

- High-CRI white light output (2000-10000K)
- 8 and 16-bit color modes: CCTRGBW, CCTHSI, CIExy, etc. Hardline DMX via XLR-5 adapter
- IP-X5 Rating (water resistant)
- Easy PSU / battery mounting on yoke
- Razor-sharp cuts and rotating barrel

- Wireless control via integrated LumenRadio
- Smooth and Sharp dimming modes
- DMX-controllable fan modes: Full, Auto, Silent, Off
- Compact and easy to hide






240327A




SPECIFICATIONS

Beam Angle19° / 36° / 50° lens tubeCCT Range2000-10000K continuous tuning + magenta/green shiftCRI/TLCI95 / 90 typical	
CRI/TLCI 95/90 typical	
757 75 (7)1661	
Control Modes CCT, HSI, RGBW, GEL, CCTRGBW, CCTHSI, CIExy, ICTHS, and more	
Dimming 100 - 0% flicker free	
Dimming Modes / Curve Smooth, Sharp / Linear, Gamma	
Light Engine DiCon Dense Matrix LED	
Power Consumption 90W max AC 80W max DC	
BTUs/hour 307 (BTUs/hour) max	
DC Input 14 - 30V DC (via 5.5mm x 2.5mm Barrel)	
AC Input 100 - 240V AC, 50 ~ 60Hz	
DMX/RDM Port TRRS (XLR-5 via adapter)	
Wireless Control Integrated LumenRadio CRMX	
USB Power Output 5V/1A (via USB-C)	
Weight Fixture: 6.7 lbs / 3.0kg (includes lens tube) Power adapter: 1.1 lbs/0.5kg	
Size (L x W x H) 14.4" x 8.6" x 11.0" / 36.6cm x 21.8cm x 27.8cm	
Mount Baby stud 5/8" female (16mm)	
IP Rating IP-X5 (water-resistant)	
Thermal Design Controllable fan	<u> </u>
Operating Temperature 32 - 104°F / 0 - 40°C	
GoBo Size M Size (Diameter 66mm / Max Image: 48mm / Max Thickness: 1mm)	

PHOTOMETRIC DATA





ACCESSORIES







G3 Leko Gobo Set of 4



G3 Leko Iris



Flexible Energy Source 270



D-Tap Cable - 24" Curled